

## NEW CALIPER WITH HIGH ACCURACY AND PRESET FUNCTION



This digital caliper is available in 2 lengths.  
**150mm/6" 200mm/8"**

The display is shown in **0.005mm/0.0002"**

The preset function is especially useful for internal measurement with FMS caliper attachments and measurement inserts. After presetting the display, measurement is the actual dimension and no calculations are necessary.

### FEATURES

- Preset function
- Data output
- 3V battery (CR2032)
- Zero-setting at any position
- Absolute and relative measurement conversion at any position.

### ACCURACY

110-051 (150mm)  $\pm 0.015\text{mm}/0.0006''$   
110-052 (200mm)  $\pm 0.020\text{mm}/0.0008''$

**The 2 high precision calipers can of course be used as normal calipers but when used with FMS caliper attachments see below.**



Caliper no. 110-051 mounted with FMS insert holders type 10A and pressure device 40A for external measurement ready for FMS inserts.



Caliper no. 110-051 mounted with FMS insert holders type 10A and pressure device 40A for internal measurement ready for FMS inserts.

### Instruction for presetting:

Press the yellow SET button until the first digit starts to blink. Push until the digit required appears. The number increases with each push. To continue to the next digit simply hold the SET button down until the second digit blinks. The number increases with each push. Simply continue this procedure until the preset value is achieved. The caliper should be locked until presetting is complete.

The presetting function is particularly useful when measuring internal thread pitch diameters as the calibration plate value can be preset and the caliper display will be the actual dimension.